## **OPS-PCIC-5WH/5WS**

Integrated and removable single board computers with Dual Core Intel i5 processor for unprecedented computing power

Enjoy seamless integration with these internal Intel Core i5-based PCs that adhere to the Open Pluggable Specification (OPS) and increase the operational flexibility of a compatible NEC display for any digital signage application.



## Highlights

- No external connections required. DVI video, stereo audio, RS232 control and power are all passed internally from display to OPS device, allowing for seamless, hidden integration and simplified installation
- **Commanding 2.5 GHz Dual-Core Intel i5 CPU**, utilizing the Intel Sandy Bridge architecture, provides enough processing power to run the highest end content with uninterrupted playback
- **Durable and protected** with an all-stainless steel chassis and integrated redundant cooling fans to protect the unit during installation, operation and service
- Flexible internal configuration with choices of solid state or disk drives
- Full 1080p playback ensures reliable, crisp and clear content
- DisplayPort output allows for multi-display support
- Four USB ports allow you to connect compatible devices
- Full networking capabilities through the integrated Ethernet connection
- 3-year warranty matches that of the display

		Quick-Service Restaurants	Education		With SB-02AM Adaptor:
				NEC P Series, V422, V462, V551, V651,	
	IDEAL	Digital Signage	Corporate	COMPATIBLE	X463UN, X551UN
	FOR	Rental & Staging	Medical	DISPLAYS	Without SB-02AM Adaptor:
		High-Load Situations	Retail		without SB-02AM Adaptor:
			Retail		X461S, X551S

OPS-PCIC-5WH: Windows 7 Embedded OPS-PCIC-5WS: Windows 7 Embedded				
2.5 GHz Intel Dual Core i5 (2510E)				
Integrated HD3000				
2GB DDR3				
OPS-PCIC-5WH: 250GB HDD OPS-PCIC-5WS: 32GB SSD				
Internal DVI, External DisplayPort				
Internal Stereo, External DisplayPort				

Gigabit Ethernet		
USB 2.0 (4)		
1080p video playback, MPEG/2, H.264, WM9		
16VDC Input Voltage, Power Dissipation (60W)		
32° - 104°F / 0° - 40°C		
80% maximum relative humidity, non-con- densing		
7.1 x 1.2 x 4.6 in. / 180 x 30 x 118mm		
2.5 lbs. / 1.2 kg		
3 lbs.		
CE, FCC Section 15		

Product specifications subject to change. ©2012 NEC Display Solutions of America, Inc. All rights reserved. 25.NEC.80.GL.UN.110 rev. 062612 NEC Display Solutions 500 Park Boulevard, Suite 1100 Itasca, IL 60143 866-NEC-MORE

