

# Industrial Open Frame Monitor EOFE-R17

17" LED SVGA LCD Resistive Touch Display

## Product Features:

- 17" LED SVGA LCD Resistive Touch
- OSD control on the rear side
- Supports up to 1280 x 1024 resolution
- DC 12~24V Wide Range Power Input



## Product Specifications:

|             |                                 |                                |
|-------------|---------------------------------|--------------------------------|
| Display     | Model Name                      | EOFE-R17                       |
|             | Size/Type                       | 17" LED SVGA                   |
|             | Resolution (pixels)             | 1280 x 1024                    |
|             | Number of Colors                | 16.7M                          |
|             | Brightness (cd/m <sup>2</sup> ) | 350                            |
|             | Backlight lifetime              | 50000hrs                       |
|             | Viewing Angle                   | 85°H/85°V                      |
| System      | VGA                             | 1                              |
|             | DVI                             | Optional                       |
|             | HDMI                            | None                           |
|             | DP                              | None                           |
|             | S-Video                         | None                           |
|             | OSD Control                     | 5 Keys                         |
|             | Others                          | RS-232 or USB interface        |
| Power       | Power Input                     | DC 12~24V                      |
|             | Power                           | 2 pins terminal block          |
| Mechanical  | Construction                    | Steel                          |
|             | IP rating                       | None                           |
|             | Mounting                        | Panel mounting, VESA 100 x 100 |
|             | Dimension (mm)                  | 364.6 x 290.6 x 36             |
|             | Net weight                      | 4.82 kg                        |
| Environment | Operating Temperature           | 0~50°C                         |
|             | Storage Temperature             | -20~60°C                       |
|             | Storage humidity                | 5 to 95% @40°C, Non-condensing |
|             | Certification                   | CE/FCC Class A                 |

Note: All Specifications are subject to change without prior notice!

