

# T25 Thermal Printer



## Highlights

- Drop in Front Facing paper loading with Autocutter
- Small, space saving footprint
- Print Speeds up to 200mm per second
- Ideal for Universal Printer Base

## T25 Front Loading Thermal Printer

The unique space saving T25 Thermal Printer with front loading and printing is perfect for the Universal Printer Base. This fast robust printer delivers great value and great speed.





## T25 Specifications

Print Method		Direct Thermal
Print Speed		200mm/sec
Print Resolution		180 DPI
Dot Pitch		512 dots/line (72mm line)
Paper	Type	Thermal Paper
	Width	79.5mm
	Thickness	0.06 ~ 0.09mm
	Roll Diameter	Max 83mm
	Roll Core Inner	12.5mm +/- .5mm
Reliability	Tph Life	160Km
	MCBF	60,000,000 Lines
Auto Cutter		1,500,000 Cuts
Sensor		Paper End, Paper Low, Cover Open, Black Mark Sensor (option)
Interface		Serial/USB, Parallel/USB, Ethernet/USB
Emulation		ESC/POS COMPATIBLE
Driver		Window Printer Driver (7, XP, POSReady09, POSReady 7, Linux)
Power	Type	External SMPS
	AC	100-240VAC 50/60Hz
	DC	24Vdc/2.5A
Dimension	W x D x H	4.68 x 8.3 x 5.2 in
Weight		1.4kg / 3.09lbs
Temperature	Operation	5 ~ 40C
	Storage	-20 ~ 60C

