



# 5500L 55" Interactive Digital Signage Touch Display

**The 5500L Interactive Digital Signage (IDS) display** combines a precision Elo touch screen with a professional-grade, large format LCD panel. The 5500L offers System Integrators, Value-Added Resellers and Software Developers a high-performance touch solution for interactive digital displays in high traffic environments.

The 55" 5500L is part of a family of large-format touch displays which bring interactivity to digital signage. The 5500L features a choice of two sensitive, accurate touch-screen technologies, each with pure-glass construction for visual clarity:

- Optical touch provides multi-touch (up to 4 touches) and gesture support (Microsoft® Windows 7 required)
- IntelliTouch single-touch surface acoustic wave touch-screen stands out for consistent reliability

The display is housed in a highly durable steel chassis for a long life of reliable and durable performance in almost any public access location. Optical touchscreen technology recognizes touch with a finger, gloved hand, prosthetic, stylus, card or pen while the IntelliTouch touchscreen recognizes touch by a finger, gloved hand, prosthetic, or virtually any soft stylus. With these technologies the result is an efficient display canvas for almost any commercial application. In addition, the 5500L sports a thinner profile (4.8") and an LED-based LCD panel which reduces power consumption and heat output.

Optional high performance computer modules are well-suited for running interactive media and are available with a choice of two processing models: ECM1 with the Intel Celeron Dual-Core 2.2GHz and ECM2 with the Intel Core 2 Duo 3.0GHz. The computer modules are field-installable, easily sliding into a dedicated bay behind the touch display and locking into place with two thumbscrews. These modules make the 5500L a reliable platform that is interoperable with content management servers and support optimal partitioning of locally cached and network stored content.

## Benefits

- Professional-grade hardware provides improved durability withstands rigors of public use over "consumer-type" TV displays
- Power and display control functions can be locked out to prevent tampering
- Built-in speakers provide audio expansion capabilities
- Choice of reliable and resilient optical or IntelliTouch touchscreen technologies delivers an exceptional touch experience
- Landscape and portrait orientations allow flexible configurations to suit a variety of design layouts
- Advertising and content effectiveness measured in real-time with interactive feedback
- Available optional slide-in integrated computer module with no cables



# 5500L 55" Interactive Digital Signage Touch Display

Model	5500L
Active Display Area	47.6" x 26.8" (1209.6 x 680.4mm)
Dimensions*	50.8" x 29.9" x 4.8" (1290.9 x 761.7 x 122.4mm)
Touchscreen technology	IntelliTouch surface acoustic wave; optical multi-touch
LCD Technology	Active matrix TFT LCD with LED backlight
Diagonal Size	54.6"
On-Screen Display (OSD)	Accessible through switches on the rear, or through the standard Elo OSD control box accessory (sold separately). Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, Auto Adjust, H-position, V-position, Maintain Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Mounting, OSD H-Position, OSD V-Position, Volume, Mute, Recall Defaults, Video Source, Audio Source, ECM MDC; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power
Monitor Diagnostics Control	RS-232 interface or through Elo computer module docking connector
Mounting Options	VESA MIS-F 600x400, Y, 6, 90 mounting provided on rear. Optional stand accessory is available.
Native Resolution	1920x1080
Aspect Ratio	16:9
Preset Video Timings	640x480 60Hz; 720x480 60Hz; 720x576 50Hz; 800x600 56, 60Hz; 1024x768 60Hz; 1280x720 50, 60Hz; 1280x960 60Hz; 1280x1024 60Hz; 1360x768 60Hz (does not scale; image is centered on panel and the remaining active area is filled with black); 1366x768 60Hz; 1440x900 60Hz; 1680x1050 60Hz; 1920x1080 60Hz
Number of Colors	1073.7 million
Brightness (typical)	LCD Panel: 450 nits; IntelliTouch: 405 nits; optical multi-touch: 405 nits
Response Time (gray to gray) (typical)	6.5 ms
Viewing Angle (typical)	Horizontal: ±89°; Vertical: ±89°
Contrast Ratio (typical)	4000
Video Interfaces	Analog VGA on Female DE-15 connector; HDCP-capable HDMI 1.3 on HDMI Type A receptacle connector; Input Video Horizontal Sync frequency range: 31.5 - 80 KHz; Input Video Vertical Sync (frame rate) frequency range: 47-63 Hz
Power	Input power connector: IEC 60320 C14; Input power signal specifications: 100-240VAC 50/60Hz; Power Consumption (Typical): Monitor only: ON, max audio, 100V/60Hz: 145W; SLEEP, 100V/60Hz: 15W; OFF, 100V/60Hz: 3.5W Monitor with ECM1 Computer Module: S0 - ON, max audio, 100% CPU load, 100V/60Hz: 238W; S3 - STANDBY, 100V/60Hz: 17W; S5 - OFF, 100V/60Hz: 13.2W Monitor with ECM2 Computer Module: ON, max audio, 100% CPU load, 100V/60Hz (S0): 268W; S3 - STANDBY, 100V/60Hz: 17W; S5 - OFF, 100V/60Hz: 13.2W
Audio	Internal speakers: a pair of 10W stereo speakers; Input audio connector: 3.5mm TRS jack; Input audio signal range: 1Vrms max stereo signal (standard PC line out) ; Headphone output connector: 3.5mm TRS jack; Headphone output signal (at 1KHz): delivers 90mW of power into a 32-ohm stereo load
Weight	Unpackaged: Weight without Computer Module: 88.8lb (40.3Kg); Weight with Computer Module: 94.6lb (42.9Kg); Packaged (Computer Module ships separately); Weight: 119.7lb (54.3Kg)
Shipping Dimensions	14.2" x 51" x 38.2" (36 x 145 x 97 cm)
Temperature	Operating: 32°F to 95°F (0° C to 35° C); Storage: -4°F to 122°F (-20° C to 50° C)
Humidity (non-condensing)	Operating: 20% - 80%; Storage: 10% - 90%
Regulatory approvals and declarations	Argentina S-mark; Australia C-Tick; Canada cUL, IC; China CCC; Europe CE; Japan VCCI; Korea KC; Mexico NOM; Russia & CIS GOST; Taiwan BSMI; United States UL, FCC; International CB
Warranty	3 years
MTBF	50,000 hours demonstrated

\*See dimensional drawings for details.

To find out more about Elo's extensive range of touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

North America	800-ELO-TOUCH	Europe	Asia-Pacific	Latin America
TE Touch Solutions	Tel 1-650-361-4800	Tel +32 (0)16 35 21 00	Tel +81 (45) 478-2161	Tel 786-923-0251
301 Constitution Drive	Fax 1-650-361-4722	Fax +32 (0)16 35 21 01	Fax +81 (45) 478-2180	Fax 305-931-0124
Menlo Park, CA 94025-1110	customerservice@elotouch.com	elosales@elotouch.com	www.tps.co.jp	www.elotouch.com.ar



Tyco Electronics Corporation and its Affiliates in the TE Touch Solutions business unit of the TE Connectivity Ltd. family of companies (collectively "TE") reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Elo (logo), Elo TouchSystems, IntelliTouch, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks of the TE Connectivity Ltd. family of companies. Windows is a trademark of Microsoft Corporation.

Copyright 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company. All rights reserved. 11/11

