

- Big, bright, and beautiful "lifesize" scale delivers interactive brand experiences
- Thin, commercial-grade touchscreen ideal for wayfinding, whiteboard, and other office applications
- Optional plug in Intel Core i3/i5 processors running Microsoft Windows®
- Infrared for up to 10 points with "Built for Touch" reliability



7001LT 70" Interactive Digital Signage (IDS) Touch Display

The 7001LT Interactive Digital Signage display combines an infrared multitouch touchscreen with a professionalgrade, large format display in a slim, integrated package. For retail, hospitality, commercial real estate, education and other commercial applications, the large wide-screen format offers a high-quality, interactive canvas for attracting and engaging consumers. The 7001LT offers system integrators and value-added resellers (VARs) a high performance solution that is easy to deploy and maintain. With a total thickness of 3.7 inches (94mm), the 7001LT is compliant with the ADA requirement of less than 4" protrusion for wallmounted products when used with a compatible wall-mount.

With a 500 nit LED panel, the 7001LT is a bright, high quality display suitable for public environments. The infrared touchscreen enables up to ten simultaneous touches for multi-user interaction. This touch technology offers a fast and extremely sensitive response similar to the experience

on mobile devices and is compatible with Windows® 7 and Windows® 8 operating systems. The touch-screen is 4mm thick with fully tempered glass. The 7001LT smart video sensing technology automatically detects new video sources and automatically switches to them.

Optional, high performance computer modules are available which turn the 7001LT into a completely integrated all-in-one computer—without the need for any cables or additional mounting hardware. Computer modules are available in a choice of two models: ECMG2-i3 based on a 3.3GHz Intel® Core i3 processor and HD2500 graphics; and ECMG2-i5 based on a 3.6GHz Intel Core i5 processor and HD4000 graphics. The high performance, commercial-grade computer modules make the 7001LT a reliable platform that is interoperable with most content management servers and supports optimal partitioning of locally cached and network streamed content.



Benefits:

- Professional-grade hardware including tempered touchscreen glass to withstand the rigors of public use
- Thin (<4" mounted) design is attractive and compliant with ADA and IBC protrusion requirements
- Reliable, integrated digital signage solution with optional NFC and RFID scanners and webcam kits
- 3 year standard warranty with optional 2 year extended warranty.
 On-site advance replacement exchange option available in USA
- Remote management capability for device hardware with support for future cloud applications
- Intel OPS compliant with available adapter kit
- Flexible mounting in portrait, landscape and table-top orientation

About Elo

Elo founders pioneered the touchscreen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touch monitors, and all-in-one touch computers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

7001LT 70" Interactive Digital Signage (IDS) Touch Display

Specifications				
Model	7001LT			
Form Factor	Interactive Digital Signage			
Bezel Color	Black			
Active Display Area (W x H)	60.6" x 33.7" (1538.9mm x 865.6mm)			
Dimensions* (W x D x H)	62.9" x 3.7" x 36.4" (1600mm x 94mm x 925 mm)			
Display Technology	Active matrix TFT LCD with LED backlight, 16.7 million colors, 8 ms response time (tr+tf)			
Diagonal Size	69.5"(176.6cm)			
Mounting Options*	VESA 4-hole mount per MIS-F, 600, 600, 8MM Optional thin, tilting wall mount E248743 available to ensure ADA and IBC compliance			
Native Resolution	1920x1080 60Hz (Full HD), 16:9 aspect ratio; Other resolutions supported.			
Brightness (typical)	LCD Panel: 500 nits; with touchscreen: 450 nits			
Viewing Angle (typical)	Horizontal: ±88°; Vertical: ±88°			
Contrast Ratio (typical)	5000:1			
Video Inputs	Analog VGA on Female DE-15 connector; HDCP-capable HDMI 1.3 on Type A connector; DisplayPo 1.1a connector; Input Video Horizontal Sync frequency range: 53-70KHz; Input Video Vertical Sync (frame rate) frequency range: 47-63Hz			
Input Power Connector	IEC 60320 C14			
Power Consumption (typical)	Monitor Only: 110V at 60Hz, ON: 201W, SLEEP: 12.5W, OFF: 1.5W; 230V at 50Hz, ON:198.0W, SLEEP:12.5W, OFF: 2.0W			
Audio	Internal Speakers: 4 x 5W stereo speakers to allow Stereo configuration in portrait and landscape mode Input audio connector: 3.5mm TRS jack; Input audio signal range: 1Vrms max stereo signal (standard PC line out); Headphone output connector: 3.5mm TRS jack			
Weight	Unpackaged, monitor only: 149.5 lb (67.8kg)			
Shipping Dimensions (W x D x H)	70.6"x15.2x45.2"(1794 x 386 x 1149 mm)			
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)			
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%			
Regulatory approvals and declarations	UL, FCC; cUL, IC; CB; CE; VCCI; C-Tick; NOM CoC; GOST; BSMI; KC; e-Standby; CCC, China RoHs With RFID: UL, FCC; CE			
Accessories	MSR(E545781), NFC Adapter (E918074), OPS Kit (E102270), Replacement OSD Controller (E483757) Replacement Cable Kit (E000263), Wall Mount Kit (E248743), Webcam (E688656)			
Warranty	3 years standard. On-site exchange (U.S. only) and extended warranty available			
MTBF	50,000 hours demonstrated			

^{*}See dimensional drawings for details

Ordering Information

Model	Part Number	Description
7001LT	E008823	70-inch LED Infrared multi-touch Interactive Digital Sign

Optional Computer Modules

Model	Part Number	Processor	RAM	HDD	OS
ECMG2-i3	E776797	Intel Core i3 3.3GHz HD2500	2GB	320GB	No OS
	E487570	Intel Core i3 3.3GHz HD2500	2GB	320GB	Windows 7
ECMG2-i5	E272400	Intel Core i5 3.6GHz HD4000	4GB	320GB	No OS
	E584199	Intel Core i5 3.6GHz HD4000	4GB	320GB	Windows 7
	E009007	Intel Core i5 3.6GHz HD4000	4GB	320GB	Windows 8.1

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America Elo Touch Solutions 1033 McCarthy Boulevard Milpitas, CA 95035

800-ELO-TOUCH Tel +1 408 597 8000 Fax +1 408 597 8050 customerservice@elotouch.com elosales@elotouch.com

Europe Tel +32 (0)16 70 45 00 Fax +32 (0)16 70 45 49

Asia-Pacific Tel +86 (21) 3329 1385 Fax +86 (21) 3329 1400 www.elotouch.com.cn Latin America Tel 786-923-0251 Fax 305-931-0124 www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2015 Elo Touch Solutions, Inc. All rights reserved. DS000107, rev A 03/15

