

19" Zero-Client Touch Screen Monitor

CP Series

GVision's CP cloud monitors utilize Teradici's® PCoIP® TERA2 chipset and VMware View™ software to deliver a powerful and secure virtual computing solution. Designed for industrial and commercial use, GVision's cloud monitors can easily be integrated into a multitude of solutions. Our cloud based monitors eliminates the need for desktop workstations, PC's, and thin clients, and delivers an uncompromised user experience to every desk...regardless of location.

Features:

- Integrated Teradici® PCoIP® TERA2 chipset
- Stateless zero-client, no data storage
- Server-based remote imaging
- WAN optimizations built into the protocol

True Zero Client Simplicity

- No OS or hard drive
- Improved security
- Increased costs savings



Specifications	
LCD Display	19" TFT active matrix panel
Max. Resolution	SXGA 1280 x 1024
Contrast Ratio	1000:1 (Typ.)
Brightness	350 nits / LED
Response Time (Tr+Tf)	5 ms (Typ.)
Display Color	16.7M
Effective Display Area	376.4 (H) x 301.1 (V) mm
Viewing Angle (CR≥10)	170°(H) x 160°(V) (Typ.)
Lamp Life (hr) / Backlight	50,000
Video Output	(1) DVI-D
Ethernet	(1) RJ45
USB	(4) USB 2.0
Touch Panel	5-wire resistive
Power	Universal 100~240V, 50~60 Hz 1.5A AC input
Operating	Temp: 0°C ~ 40°C (32°F ~ 104°F); Humidity: 10% ~ 90% (no condensation); Altitude: To 10,000 feet
Storage	Temp: -20°C ~ 60°C (-4°F ~ 140°F); Humidity: 10% ~ 90% (no condensation)
Dimensions (WxHxD)	438.0 x 417.5 x 180.0 mm
Weight (Net)	8 kg
Certification	EMC: CE/FCC; Safety: UL / c-UL / TUV (AC type); Other: RoHS/WEE

Gvision-USA

Address: 20532 Crescent Bay Drive, Suite 104, Lake Forest, CA 92630 **Tel:** 888-651-9688

Web: www.gvision-usa.com **Email:** info@gvision-usa.com