

## D24ZD

### Desktop Projected Capacitive Touch Displays

#### Features:

- Zero bezel touch screen
- Water and dust resistant
- Zero pressure touch activation
- Multiple sizes available - 10", 15", 17", 19", 22" and 24"
- Wide screen sizes also available in 15" and 19"
- 3 year warranty



#### Specifications

<b>Part Number</b>	<b>D24ZD</b>
<b>Display Size</b>	23.8 in
<b>Display Area</b>	20.7 x 11.7 in (527 x 296 mm)
<b>Panel Brightness (With PCAP Sensor)</b>	300 nits (260 nits)
<b>Response Time</b>	20 ms Typical (Tr + Tf)
<b>Power Consumption</b>	35W MAX Standby ≤ 2.5W
<b>Dimensions (W x H x D)</b>	22.8 x 13.7 x 2.1 in (580.2 x 347.4 x 54.5 mm)
<b>Weight</b>	13.8 lbs (6.3 kg)
<b>Contrast Ratio</b>	3000:1
<b>Touch Material</b>	1 mm Glass
<b>Native Resolution</b>	1920 x 1080
<b>Aspect Ratio</b>	16:9
<b>Viewing Angle</b>	178°H / 178°V
<b>VESA Mount</b>	100 x 100 mm
<b>Video Inputs</b>	HDMI, DVI, VGA
<b>Backlight</b>	LED
<b>Input Power</b>	12VDC ± 5% (Adapter Input AC 100V ~ 240V, 50/60Hz)
<b>MTBF</b>	50,000 hrs
<b>Touch Type</b>	Projected Capacitive (PCAP)
<b>Touch Points</b>	10 max (Dependent on OS / Browser / Software)
<b>Touch Accuracy</b>	2 mm
<b>Touch Interface</b>	USB (B-Type)
<b>Surface Durability</b>	Mohs' 7H
<b>Audio</b>	Speakers Optional
<b>Temperature</b>	Operating: 32°F ~ 104°F (0°C ~ 40°C) Storage: -4°F ~ 140°F (-20°C ~ 60°C)
<b>Humidity</b>	Operating: 20% ~ 80% Storage: 10% ~ 90%
<b>Enclosure Material</b>	Metal Enclosure
<b>Included Accessories</b>	AC Adapter, Power Cable, VGA / USB Cables

#### Mechanical Drawing

