# KIP540(-S), KIP542(-S), KIP546(-S), KIP547(-S), KIP555(-S)

Display size
40", 42", 46",
47" or 55"

LB (KG)

Max load **75lb (34kg)** 

# Portrait Kiosk Enclosure

Fits 40", 42", 46", 47", and 55" Displays up to 4" (101mm) Thick

Make a statement with Peerless-AV's versatile digital signage kiosk. Designed to support ultra-thin or thicker commercial displays, this kiosk accentuates the sleek look of the display while providing ample space to integrate a media player, interactive touch system, etc, to create a complete interactive kiosk experience. Paired with a wide range of aesthetic options, this modular line of kiosks makes it easy to execute any advertising or branding strategy.

Displaying digital signage content has never been easier!

### **Additional Features**

- Eight point adjustment to quickly position the display within the kiosk window for a flush alignment
- Accommodates ultra-thin or deeper commercial displays up to 4" (101mm) thick, while accentuating slim kiosk design
- ✓ VESA® 200 x 200 up to 800 x 400mm compatible
- Thermostat controlled circulation fans ensure proper airflow within the kiosk
- Secured doors allow convenient access to the display, media player and other internal components for easy installation and maintenance
- Stand-alone kiosk enclosure or fully integrated with display, media player, power and thermal management, etc.
- Supports a wide range of aesthetic options including glass/acrylic, multiple colors, vinyl wraps, etc. to best match environment or promote brand strategy
- Pre-assembled to simplify installation of entire solution





Fits most 40", 42", 46", 47" and 55" displays up to 4" (101mm) thick

KIP540(-S) Portrait Kiosk Enclosure fits 40" Displays up to 4" (101mm) Thick KIP542(-S) Portrait Kiosk Enclosure fits 42" Displays up to 4" (101mm) Thick KIP546(-S) Portrait Kiosk Enclosure fits 46" Displays up to 4" (101mm) Thick KIP547(-S) Portrait Kiosk Enclosure fits 47" Displays up to 4" (101mm) Thick KIP555(-S) Portrait Kiosk Enclosure fits 55" Displays up to 4" (101mm) Thick
--

# **Product Specifications**

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS	
KIP540/KIP542(-S) KIP546/ KIP547(-S) KIP555(-S)	28.00" x 72.12" x 20.50" (711 x 1832 x 521mm) 34.00" x 72.12" x 20.50" (864 x 1832 x 521mm) 34.00" x 78.12" x 20.50" (864 x 1984 x 521mm)	165lb (75kg) 181lb (82kg) 196lb (89kg)	75lb (34kg)	Powder Coat	KIP540-S, KIP542-S,	Gloss black Silver

# **Package Specifications**

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
KIP540/KIP542(-S) KIP546/ KIP547(-S) KIP555(-S)	48.00" x 78.00" x 40.00" (1219 x 1966 x 1016mm) 48.00" x 78.00" x 40.00" (1219 x 1966 x 1016mm) 48.00" x 83.00" x 40.00" (1219 x 2108 x 1016mm)	212lb (96kg) 228lb (103kg) 244lb (111kg)	KIP540: 735029297314 KIP540-S: 735029297321 KIP542: 735029297338 KIP542-S: 735029297345 KIP546: 735029296737 KIP546-S: 735029296775 KIP547: 735029296744 KIP547-S: 735029296782 KIP555: 735029296751 KIP555-S: 735029296805	Kiosk with display mounting hardware	1

Accessories PVP1000-PL6: Surge Protector with Six Outlets

Agion antimicrobial protection:

Agion® antimicrobial\* finish available to assist in controlling the spread of infections. Contact Peerless-AV Customer Care for more information.

\*Antimicrobial protection is limited to the treated article and does not protect a user against disease causing bacteria. Always clean products thoroughly after each use.


CL-SCG200: Screen Cleaning Gel

**DEB-HD10:** 32' (10m) High Speed HDMI® Cables with Ethernet

KioskBuilder™:

Build your own Integrated Kiosk @ kiosks.peerless-av.com including integration services, flat panel display, media player, content management software, power protection, thermal management, display protection, vinyl graphics, etc.

All dimensions = inch (mm)



MODEL NO.	DIMENSION "A"	DIMENSION "B"	DIMENSION "C"	DIMENSION "D"	DIMENSION "E"	DIMENSION "F"	DIMENSION "G"
KIP540	34.97" (888mm)	19.67"(500mm)	6.80"(173 mm)	.38"(10mm)	28.00"(711mm)	72.12"(1832mm)	20.50"(521mm)
KIP542	36.72"(933mm)	20.65"(525mm)	6.80"(173 mm)	.38"(10mm)	28.00"(711mm)	72.12"(1832mm)	20.50" (521mm)
KIP546	40.20"(1021mm)	22.61"(574mm)	6.80"(173 mm)	.38"(10mm)	34.00"(864mm)	72.12"(1832mm)	20.50"(521mm)
KIP547	41.07"(1043mm)	23.10"(587mm)	6.80"(173 mm)	.38"(10mm)	34.00"(864mm)	72.12"(1832mm)	20.50"(521mm)
KIP555	48.05"(1220mm)	27.03"(686mm)	6.80"(173 mm)	.38"(10mm)	34.00"(864mm)	78.12"(1984mm)	20.50"(521mm)

# **Architect Specifications**

The Portrait Kiosk Enclosure shall be a Peerless-AV model KIP540(-S), KIP542(-S), KIP546(-S), KIP547(-S) or KIP555(-S) and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

#### Peerless-AV

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

#### Peerless-AV Europe

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

#### Peerless-AV de México

Ave de las Industrias 413 Parque Industrial Escobedo Escobedo, N.L., Mexico 66050

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360

