ST660(P)





Display size **39"-80"**



Max load **200lb (91kg)**

SMARTMOUNT.

Universal Tilt Wall Mount

FOR 39" TO 80" DISPLAYS


The SmartMount® Universal Tilt Wall Mount series offers the most versatile installation features and mounting options. Horizontal and vertical adjustment abilities allow for post installation leveling and side-to-side positioning, making it easier than ever to find the perfect TV position. Lock the tilt angle at installation to prevent tampering or moving with the IncreLok™ tilt technology. Security screws provided in the ST660 models deter tampering and theft. The open wall plate design offers total wall access, increasing the electrical and cable management options. The display can now simply be installed by a single person with the Hook-and-Hang™ system. The Easy-Glide™ adaptors hook onto the wall plate for an overall quick, simple, and secure installation.

The ST660's adjustable viewing feature provides 15° of forward tilt and 5° backward tilt, creating the most optimal viewing angle.



Additional Features

- ☑ Universal mount fits displays with mounting patterns up to 824 x 405mm (32.44" W x 15.95" H)
- Adjustable 15° forward tilt and 5° backward tilt for finding the optimal viewing angle
- Easy-Grip[™] ratcheting handle locks tilt angle into place
- ✓ Included IncreLok[™] feature offers fixed tilt lock in 5° increments when used
- Up to 0.25" (6mm) of vertical adjustment on each universal display adaptor bracket for post-installation leveling and height adjustment fine-tuning
- Horizontal display adjustment up to 8.00" (203mm) for centering display on wall
- Mounts to wood studs, concrete, cinder block or metal studs (metal stud accessory required)
- Includes all necessary wall and display attachment hardware
- ☑ Integrated security options available
- Design is UL listed and tested to four times stated load capacity



OPEN WALL PLATE
Allows total wall access, increasing
electrical and cable management options



+15°/-5° of tilt for versatile viewing angles





Please visit peerless-av.com/en-us/patents for patent information.

ST660P ST660 SmartMount® Universal Tilt Wall Mount for 39" to 80" Displays - standard models SmartMount® Universal Tilt Wall Mount for 39" to 80" Displays - security models

Product Specifications

| | DIMENSIONS (W x H x D) | PRODUCT WEIGHT | LOAD CAPACITY | FINISH | AVAILABLE COLORS |
|----------|---|-----------------|---------------|----------------------------------|------------------|
| ST660(P) | 36.54" x 16.89" x 2.62"-5.40" (928 x 429 x 67-137mm) | 8.70lb (3.95kg) | 200lb (91kg) | Scratch resistant fused epoxy | Semi-gloss black |


Package Specifications

| | PACKAGE SIZE (W x H x D) | PACKAGE SHIP WEIGHT PACKAGE UPC | | GE UPC CODE | PACKAGE CONTENTS | UNITS IN PACKAGE |
|----------|---|---------------------------------|-------------------|------------------------------|--|------------------|
| ST660(P) | 36.41" x 2.95" x 10.71" (925 x 75 x 272mm) | 11.00lb (4.99kg) | ST660: ST660P: | 735029235606 735029231875 | Wall mount, wall and display installation hardware, installation instructions | 1 |


Accessories

ACC415: Metal Stud Fastener Kit

All dimensions = inch (mm)




WALL PLATE





ADAPTOR BRACKET



Architect Specifications

The Smartmount® Tilt Wall Mount shall be a Peerless-AV model ST660(P) and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

Peerless-AV Europe

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

Peerless-AV de México

Ave de las Industrias 413 Parque Industrial Escobedo Escobedo, N.L., Mexico 66050

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360



LIT-0596 Rev.4