

## KS7200 Series



### KEY FEATURES

- Intel® Atom™ 1.8GHz Dual Core w/ 1MB L2 Cache
- Die-Cast Aluminum Alloy Housing for maximum heat diffusion
- Operates in a wide range of environments and temperatures. 14° F ~ 122° F (-10° C ~ 50° C)
- Up to 4GB of DDR3 Memory
- Precisely designed, with strict revision control to maximize the system's lifecycle
- Liquid/Splash Resistant
- Optional RAID 1
- Available in 10", 12", 15", and 17" Infrared and Resistive touch screens

#### KS7210

- 10" TFT LCD 800x600, Resistive touch display
- Intel® Atom™ D525 1.8GHz Dual Core
- Up to 4GB DDR3 RAM
- Integrated MSR

#### KS7212

- 12" TFT LCD 1024x768, Resistive touch display
- Intel® Atom™ D525 1.8GHz Dual Core
- Up to 4GB DDR3 RAM

#### KS7215

- 15" TFT LCD, 1024x768 Resistive or Infrared touch display
- Intel® Atom™ D525 1.8GHz Dual Core
- Up to 4GB DDR3 RAM
- RAID 1 and Parallel Port options, additional ports

#### KS7217

- 17" TFT LCD, 1280x1024 Resistive or Infrared touch display
- Intel® Atom™ D525 1.8GHz Dual Core
- Up to 4GB DDR3 RAM
- RAID 1 and Parallel Port options, additional ports

## Enhanced Power-Performers

Within the comprehensive KS family of fan free terminals, the KS7200 Family is a good combination of price and performance. Featuring Posiflex's patented aluminum chassis for maximum heat diffusion, an Intel® 1.8GHz Dual Core CPU, and support of Win 7 Pro among other operating systems, the KS7200 Family offers great performance, reliability and compatibility.





- Environmentally Hardened – Stringent third party HALT / HASS tested for extensive temperature cycling, vibration, drop, shock, static electricity and emission tolerance.
- Overbuilt to Overperform – Bringing the best of both worlds, where power and performance meet the rock-solid reliability required to maximize uptime and reduce costs.
- Scalable – The KS7200 Family boasts a range of terminal screen sizes in 10", 12", 15", and 17" Infrared and Resistive Touch Functions.

### About Posiflex

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- Global presence
- Two ISO 9001/9002/14001 Certified Facilities

System	KS7210 / KS7212	KS7215 / KS7217
Processor	Intel® Atom™ D525 1.8GHz Dual Core w/ 1MB L2 Cache	
System Memory	DDR3 1066MHz SO-DIMM x 1 Slot (2GB Default)	
Maximum Memory	4GB	
Power Supply	12V DC Power Adaptor, 50W	12V DC Power Adaptor, 60W
Storage Device	2.5" SATA 160GB HDD	
Supported OS	POSREADY / POSREADY 7 / WIN XP Pro / Win 7 Pro / Linux <sup>1</sup>	
Display		
LCD	KS7210: 10" TFT LCD, 800x600 KS7212: 12" TFT LCD, 1024x768	KS7215: 15" TFT LCD, 1024x768 KS7217: 17" TFT LCD, 1280x1024
Touch Function	5-Wire Resistive	5-Wire Resistive, Infrared
Brightness Control	Digital Push Button	
Tilt Adjustment	From 20° to 90°	From 15° to 70°
Dimensions		
Dimensions (WxDxH)	KS7210   Base Mount: 12.2 x 8.1 x 10.5" KS7212   Base Mount: 12.8 x 10.3 x 11.3"	KS7215   Base Mount: 14.88 x 14.33 x 11.96" Wall Mount: 14.88 x 2.19 x 11.96" KS7217   Base Mount: 16.77 x 12.83 x 16.45" Wall Mount: 16.77 x 2.19 x 16.45"
Weight (Pounds)	KS7210: 6.87 lbs KS7212: 9.22 lbs	KS7215   Base Mount: 15 lbs; Wall Mount: 12 lbs KS7217   Base Mount: 17 lbs; Wall Mount: 14 lbs
Connectivity		
LAN Port	1 x RJ-45 10/100/1000 Base-T Ethernet (2 x RJ-45 on KS7212)	
Serial Port	KS7210 - 2 x 9-pin Male d-sub, 1 x RJ-50 with 5V / 12V support KS7212 - 2x 9-pin Male d-sub, 2 x RJ-50 with 5V / 12V support	2 x 9-pin Male d-sub, 2 x RJ-50 with 5V / 12V support
CR Port	1 x RJ-11 Port Controls 2 Cash Drawers	
Standard USB	4 x USB 2.0 Type A port	6 x USB 2.0 Type A port
Parallel Port	Optional, with Cable P/N 21862033420	
RAID 1	N/A	Optional, Requires Secondary Storage Device to work
Backup Battery	N/A	Optional

<sup>1</sup>Driver Support Only

Peripherals			
Magnetic Stripe Reader - SD402	Rear Display - PD2604	Thermal Printer - PP9000	Cash Drawer - CR6300
			
Biometric or Encrypted options available	2x20 Vacuum Fluorescent Display (VFD)	80mm wide, Printing Speed: 220mm/second	Printer Driven, USB options available

### Available Services

- Standard and Extended Warranty**  
 Extend your depot warranty up to 5 years.
- Advance Exchange**  
 We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.
- OnSite Service**  
 Expert technicians will efficiently handle the complete equipment swap and return process.
- Regional Repair Depots**  
 Three regional depots assure fast turn-around time on repairs.
- Post Warranty Support**  
 Spare parts, in addition to a flat rate repair program, for post warranty needs.
- Installation Services**  
 Let our nationwide network of experts stage and install your equipment.
- OEM Design and Integration**  
 Our Product Development Team helps design equipment, for custom hardware applications.



Posiflex Business Machines, Inc.  
 30689 Huntwood Ave.  
 Hayward, CA 94544  
 P: 888-968-1668  
 F: 510-475-0982  
 sales.department@posiflexusa.com  
 www.posiflexusa.com

Posiflex designs, engineers and manufactures:

Touch Screen Terminals & Tablets | Printers | Magnetic Stripe Readers | Cash Drawers | Rear/Pole Displays