



## **PP7600**

## 3" Thermal Receipt Printer

The PP7600 features a compact and modern cube-shaped design that can easily be placed on or under a counter. An optional ambient lighting attachment (LD2000) can be attached to the base of the PP7600, which can illuminate colorful light patterns. The fun, yet practical design of the PP7600 brings quick, reliable thermal printing and color into the mundane printing operation.

## **About Posiflex**

- · Designer and manufacturer of Point-of-Service and industrial touch terminals
- · Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- · Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- · Global presence
- Two ISO 9001/9002/14001 Certified **Facilities**

PP7600 Printer Specifications	
Printing Speed	Up to 200 mm/sec
Printing Resolution	8 dots/mm, up to 576 dots/line (default 512 dots/line)
Paper Width	80 or 58 +0/-1 mm
Printing Width	64 mm (512 dots/line, default) /72 mm (576 dots/line)
Input Buffer	6KB
LED Indicator	Power; Error; Paper out
Cutter	Auto cutter
Power Supply	24V/60W
Interface	USB (True USB / Virtual COM selectable) + Serial
Dimension (W x D x H)	129 mm x 148.8 mm x 129.5 mm
International Character Set	15 international character sets (Denmark I, Denmark II, Ex-Yugoslavia, France, Germany, Italy, Japan, Korea, Latin America, Norway, Spain, Spain II, Sweden, UK, USA)
Character Code Page	23 code pages
Barcode Printing	UPC-A/E, EAN13/8, ITF, CODE39/93/128, CODABAR, QR Code, PDF417
Option	LD-2000 Ambient-lighting Attachment, LAN or Wireless Module

<sup>\*\*</sup> The product information and specifications are subject to change without prior notice.



















Posiflex Business Machines, Inc.

30689 Huntwood Ave.