

POS Terminals

EVO TP4

The EVO TP4 sets a whole new standard by offering enterprise-class build quality, P-CAP touchscreen technologies, and the latest in high-performance Intel® processors. Available with Celeron™, Pentium™, Core i3™, Core i5™, and Core i7™ processors, the EVO TP4 thrives in the most demanding environments. The EVO TP4 has an IP54 certified rating for both dust and splash resistance.



Shown with optional MSR



Key Features



Baytrail and Haswell Processors

Available with Intel Celeron, Pentium, Core i3,



Touchscreen

15" (381mm) zero bezel, projected capacitive touchscreen technology



Hard Drive

2.5" (64mm) 500GB HDD or 60-120GB SSD



Built In Cable Management

Keeps cords out of sight



EZHD Slot

Makes for quick HDD or SSD replacement



IP54 Rating

Resistant to dust buildup and splashing water



Aluminum Alloy Frame

Provides bump-free operation



Optional Accessories

Optional integrated MSR, VFD customer display, 8.4" (213mm) rear LCD display, 15" (381mm) rear LCD display, or Biometric Reader display, or Biometric reader.

MODELS	EVO-TP4D-F	EVO-TP4D-G	EVO-TP4D-H	EVO-TP4D-J	EVO-TP4D-K	EVO-TP4D-L
Processor	Intel® Celeron J1900 2.4GHz Quad Core*	Intel® Celeron G1820 2.7GHz Dual Core*	Intel® Pentium G3420 3.2GHz Dual Core*	Intel® Core i3-4330 3.5GHz Dual Core*	Intel® Core i5-4570S 3.6GHz Quad Core*	Intel® Core i7-4770S 3.9GHz Quad Core*
Chip Set	Processor Integrated	Intel Lynx Point PCH H81				
System Memory	1 x DDR3L 4GB to 8GB	1 x DDR3 DIMM 4GB to 8GB				
Hard Drive	500GB HDD or 60-500GB SSD					
Graphic Memory	Intel Gen7 up to 854MHz	Intel® HD Graphic DX11.1				
GigaLAN (10/100/1000)	1 x RJ45					
Weight (w/base)	15 lbs (6.8kg)	15.4 lbs (7kg)				
Electrical	65W/19V	120W/19V				

PORTS	EVO-TP4D-F	EVO-TP4D-G	EVO-TP4D-H	EVO-TP4D-J	EVO-TP4D-K	EVO-TP4D-L
Parallel	1					
USB	5 x USB Type A (USB 3.0 / 2.0 x1, USB 2.0 x4)	6 x USB Type A (USB 3.0 / 2.0 x2, USB 2.0 x4)				
Serial	3 x RJ45 COM3 with 5V/12V	3 x RJ45 COM3 with 5V/12V, 1 DB9				
VGA	1					
Cash Drawer Port	1					
Speakers	2					

PHYSICAL	
Housing	Die Cast Aluminum
Dimensions (w/base) (WxDxH)	14.21" x 9.76" x 13.27" (361mm x 248mm x 337mm)
VESA Wall Mountable	3.9" x 3.9" (100mm x 100mm)
Tilt Angle	0° – 90°
Housing Color	Black
Bezel	TruFlat Zero Bezel
LCD Display	15" (381mm) LED LCD
Touch Technology	Projected Capacitive (P-CAP)

ENVIRONMENTAL	
Ingress Protection	IP54-Resistant to dust buildup and splashing water
Operating Temperature	32°F to 95°F (0°C to 35°C)
Humidity	20% to 80% non-condensing
Warranty	3-year warranty with free *2-day Advance Exchange Service
Certifications	FCC, Class A, CE, LVD, RoHs, NOM
Supported OS	Win 7, Win 8, Win 10, Available with no O/S

WARRANTY EXTENSION AND UPGRADES	
ZWE-TPC	2-Year Warranty Extension
ZOE-TPC3	**3-Year Overnight Exchange
ZOE-TPC5	**5-Year Overnight Exchange

OPTIONAL ACCESSORIES	
EVO-MR4	3 Track Magnetic Stripe Reader with USB interface
EVO-BR4	Integrated U.are.U 4500 BIO Reader
EVO-RD4-VFD	Integrated 2x20 VFD Customer Display
EVO-RD4-LCD8	Integrated Rear Display, 8.4" (213mm) LCD w/VGA Cable & Mount
EVO-RD4-LCD15	Integrated Rear Display, 15" (381mm) LCD w/VGA Cable and Mount
EVO-XZ4-M100	Universal VESA Mount for All Terminals and Touch Monitors

*Shipped product may include an equivalent or faster processor. Processor speeds based on Passmark® benchmark scores. Speeds shown are maximum burst speed.

**Available in USA and Canada.