

## Receipt Printers

## Sewoo Mobile Printer

The LK-P21 receipt printer is a cost effective, high performance mobile receipt printer. Featuring built-in bluetooth and an integrated rechargeable lithium-ion battery. The LK-P21 provides the performance and mobility you need.

The LK-P21 features fast direct thermal receipt printing, auto cutting, and a ruggedized exterior. Its lightweight design allows for easy carrying and reliability, perfect for mobile receipt printing. The LK-P21 is dependable, affordable and most importantly, mobile.



### RELIABLE & AFFORDABLE

Priced to beat the competition, the LK-P21 features a 1130mAh battery, and a thermal print head that lasts over 30 miles of receipts.



### COMPATIBILITY

With the ability to connect via USB, Serial, or bluetooth, plus support for ESC/POS and ZPL commands, it's the perfect solution for any software package.



### EASY PAPER LOADING

Easy drop-in thermal paper loading won't slow you down on the go



### ENERGY EFFICIENT

With its low power standby state lasting up to 10 hours, and quick 2 hour charging times, the LK-P21 will never leave you looking for a charge



<b>PART NUMBER</b>	LK-P21
<b>INTERFACE SPECIFICATIONS</b>	
Interface Details	USB 2.0/Serial RS232C/Bluetooth
Emulation	ESC/POS, CPCL, ZPL Command compatible
Print Method	Direct Thermal
Printing Speed	3.14"/sec (80mm/sec)
Print Resolution	203 DPI x 203 DPI
Sensors	Cover Open, Paper End
Reliability	TPH Life 31 miles (50Km) Rated for 4' Drop to Concrete

<b>PAPER</b>	
Type	Thermal Paper
Width	2.2" (58mm)
Thickness	0.002" (0.06mm) - 0.0035" (0.09mm)
Roll Diameter	Max 1.57" (40mm)
Roll Core Inner Diameter	0.492" (12.5mm) ± 0.019" (0.5mm)
Character Set	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page); International Characters 14
Character/Line	Font A (12 x 24) 32 columns Font B (9 x 17) 42 columns
Barcodes Supported	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, UPC-E, CODE 128, PDF 417, QR CODE, DATAMATRIX

<b>PHYSICAL</b>	
Dimension (WxDxH)	3.14" x 4.86" x 1.84" (80mm x 123mm x 46.8mm)
Weight	0.52 lbs (240g)
Color	Black
Electrical	100-240 VAC 50/60 Hz (input) 8.4 VDC/ 0.8 A (output)

Temperature	50°F to 122°F (10°C to 50°C) operating
Humidity	35% to 80% non condensing
Warranty	1-year warranty
Certifications	FCC, UL, CE, Energy Star, RoHs
Operating System	Win 7, Win 8, Win 10, Win CE, Linux, Android, iOS

<b>AUTOCUTTER</b>	
Type	Auto-retracting guillotine
Life	50,000 Cuts
Cutting Method	Full/Partial Cut