

MS246

Magnetic Stripe Reader



Full Functionality & Compact Size

The MS246 intelligent magstripe reader delivers exceptional performance in a compact housing. It can read up to 3 tracks of magnetic stripe card data regardless of swiping direction or speed. The MS246 is ideal for POS, Security, Loyalty and other applications.

Easy To Use & Install

The uniquely designed flat housing allows for mounting in different orientations by using threaded inserts or Velcro. The 6-foot cable exits through the side, increasing flexibility in mounting options. The MS246 provides easy USB connectivity and OPOS driver support.

Many Programmable Features

The MS246 is a fully programmable reader and output format can be customized with its own user friendly Windows-based MSR Reader Configuration Manager. For example, after reading and validating card data, the unit can be programmed to parse the data, insert control characters, and add prefix/suffix characters while maintaining data integrity through vertical and longitudinal error checking.

Features

- USB-KB or USB-HID Interface
- User Friendly Configuration Software
 - Reads up to 3 tracks of information
 - Reliable for a minimum of 1,000,000 passes
- Signifies successful reads with a beeper and tri-color LED indicator
 - Can be used free standing or mounted
- Threaded inserts for easy and flexible mounting
 - 2 year warranty from date of invoice
 - OPOS driver is available

Electrical

Magnetic TTL

Power +5 VDC +/-10% (50mV ripple maximum). Ground 0VDC (GND). Chassis ground connected to GND and magnetic head case.

Operating Current

1mA per track maximum when reading a card, About 70mA for decoded magnetic stripe

Environmental

Operating Temperature

32°F to 131°F (0°C to 55°C)

Storage Temperature

-22°F to 158°F (-30°C to 70°C)

Humidity

Maximum 95% non-condensing

Reliability

Magnetic Head Life

1,000,000 passes minimum

Rail and Cover Life

1,000,000 passes minimum

Conformance

ISO 7811 1-6

Warranty

2 years, parts and labor

Mechanical

Magnetic Stripe Formats

ISO 7811 and AAMVA

Swipe Speed

5 to 50 inches per second, bi-directional

Card Thickness

.015 to .045 inches.

Slot Width

.050 inches (1.37mm)

Indicators

Tri-colored LED, beeper

Interfaces

USB-KB, USB-HID

Dimensions

Length: 3.94 inches (100mm)

Width: 1.38 inches (35mm)

Height: 1.18 inches (30mm)

Weight

Approximately 7 oz

Cable Length

6-foot side exit cable

Unitech America

Los Angeles, Houston, Mexico City
<http://www.ute.com> e-mail: inquiry@ute.com
<http://latin.unitech-adc.com> e-mail: info@latin.ute.com

Unitech Asia Pacific

Taipei
<http://www.unitech-adc.com> e-mail: aidcsales@tw.ute.com

Unitech Japan

Tokyo
<http://www.unitech-japan.co.jp> e-mail: sales@jp.ute.com

Unitech Europe

Tilburg / Netherlands
<http://www.unitech-europe.com> e-mail: sales@eu.ute.com

Unitech Greater China

Beijng, Shanghai, Guang Zhou, Xiamen
<http://www.ute.com.cn> <http://www.ute.cn> unitech@cn.ute.com
Taipei <http://adc-utt.unitech.com.tw> barcode@tw.ute.com

Head Office

Taipei
<http://www.unitech-adc.com> e-mail: marketing@tw.ute.com