

# 24" (23.6" viewable) Full HD Optical Touch Monitor

Intuitive Dual-Point Touch Design

**TD2420**



Interact with your monitor as if it were a smartphone or iPad. Great for commercial kiosks, interactive POS display, and educational applications, as well as in-home gaming and photography, the ViewSonic® TD2420 24" (23.6" viewable) dual-point touch Full HD LED monitor lets users execute two-finger pinches, taps and swipes for fast, intuitive navigation. 20M:1 MEGA Dynamic Contrast Ratio, 1080p resolution and integrated speakers engage and delight with sharp images, outstanding color accuracy, and crystal clear sound. Whether enjoyed at home or deployed in a high-traffic commercial setting, its scratch-resistant surface stands up to heavy use and safeguards its high quality touch experience.

#### **Key Features:**

Full HD 1080p resolution and 20M:1 MEGA Dynamic Contrast Ratio

Dual-point optical touch and Windows 7 compatible

8H scratch-resistant surface hardness

DVI, VGA, and dual-port USB hub

Dual speakers with SRS Premium Sound

#### **Designed for:**

Public display


Education

Home

Business

# 24" (23.6" viewable) Full HD Optical Touch Monitor

**TD2420**



## Specifications

<b>PANEL</b>	Type	24" (23.6" viewable) Wide Color TFT Active Matrix LED
	Display Area	20.5" horizontal x 11.5" vertical; 23.6" diagonal
	Optimum Resolution	1920x1080
	Brightness	200 cd/m <sup>2</sup> (typ.)
	Contrast Ratio	1000:1 (typ.)
	Dynamic Contrast Ratio	20,000,000:1
	Viewing Angles	170° horizontal, 160° vertical
	Response Time	5ms (typ.)
	Backlight	White-light LED
	Backlight Life	30,000 hours (min.)
Panel Surface	8H Scratch Resistant Surface Hardness	
<b>VIDEO INPUT</b>	Analog	RGB analog (0.7 / 1.0 Vp-p, 75 ohms)
	Digital	HDMI, DVI (TMDS, 100 ohms)
	Frequency	Fh: 24~82kHz, Fv: 50~75Hz
<b>AUDIO OUTPUT</b>	Speakers	2-watt (x2)
	Sync	Separate Sync
<b>COMPATIBILITY</b>	PC	PC compatibles (Windows® 7 / 8 Operating System)
	Mac®	n/a
<b>CONNECTOR</b>	Video Analog	15-pin mini D-sub (VGA)
	Video Digital	DVI-D (with HDCP), HDMI
	Audio	Audio In (3.5mm mini-jack), Headphone (3.5mm mini-jack)
	Power	Internal power board, 3-pin plug (CEE22)
<b>POWER</b>	Voltage	AC 100~240V (universal), 50 / 60Hz
	Consumption	25W (typ.)
	Optimize	22W (typ.)
	Conserve	20W (typ.)

<b>CONTROLS</b>	Front Panel Buttons	1, 2, Down, Up, Power
	OSD	Auto Image Adjust, Contrast/Brightness, Input Select, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall (See user guide for full OSD functionality)
<b>ERGONOMICS</b>	Tilt	Forward 5° / Back 20°
	Temperature	32~104° F (0~40° C)
<b>OPERATING CONDITIONS</b>	Humidity	20~90% (non-condensing)
	<b>DIMENSIONS (W x H x D)</b>	Physical with Stand
Physical without Stand		21.9 x 13.7 x 2.2 in. / 555.9 x 346.8 x 56.1 mm
Packaging		23.8 x 19.6 x 5.9 in. / 506 x 498 x 151 mm
<b>WEIGHT</b>	Net with Stand	6.6 lb. / 3.0 kg
	Net without Stand	5.2 lb. / 2.4 kg
	Gross	8.1 lb. / 3.7 kg
<b>WALL MOUNT</b>	VESA®	100mm x 100mm
<b>REGULATIONS</b>		CE, CB, BSMI, PSB, SASO, C-tick, e-standby, KC, UL/cUL, FCC-B (including ICES003), UL CoC, Mexico Energy, GOST-R/Hygienic, UkrSEPRO, TCO 5.2, Erp, CCC, China Energy, ENERGY STAR®, EPEAT Silver, WEEE, RoHS, SVHC list
	<b>RECYCLE / DISPOSAL</b>	
<b>POWER MANAGEMENT</b>		ENERGY STAR® standards, EPEAT Silver
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight.

## Optional Accessories

DVI-D to DVI-D Cable, 6FT .....	CB-00008187
DisplayPort to DVI Adapter .....	LCD-CABLE-001

## What's in the box?

TD2420 display, power cable, audio cable, VGA cable, DVI cable, USB cable, Quick Start Guide, ViewSonic Wizard CD (available in some countries only)sv



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.