

# Industrial Display Monitor ETPM-S21

## 21.5" Projected Capacitive Touch Display

### Product Features:

- 21.5" TFT LCD Projected Capacitive Touch
- Flat Front Panel IP65
- Support VGA + HDMI
- 1000-1500nits High Brightness Sunlight Readable Optional



### Product Specifications:

|             |                                 |                                  |
|-------------|---------------------------------|----------------------------------|
| Display     | Model Name                      | ETPM-S21                         |
|             | Size/Type                       | 21.5" TFT                        |
|             | Resolution (pixels)             | 1920 X 1080                      |
|             | Number of Colors                | 16.7M                            |
|             | Brightness (cd/m <sup>2</sup> ) | 400                              |
|             | Backlight lifetime              | 50000hrs                         |
|             | Viewing Angle                   | 178°H/178°V                      |
| System      | VGA                             | 1                                |
|             | DVI                             | 1                                |
|             | HDMI                            | 1                                |
|             | OSD Control                     | NONE                             |
|             | Others                          | USB interface (for touch screen) |
| Power       | Power Input                     | DC 12V                           |
|             | Power                           | AC Adapter                       |
|             | Power Consumption               | < 35W                            |
| Mechanical  | Construction                    | Aluminum Die-casting Chassis     |
|             | IP rating                       | Front IP65                       |
|             | Mounting                        | Panel mounting, VESA 100 x100mm  |
|             | Dimension (mm)                  | 557 x 345 x 51.3                 |
|             | Net weight                      | 7.5 kg                           |
| Environment | Operating Temperature           | -10~60°C                         |
|             | Storage Temperature             | -20°~60°C                        |
|             | Storage humidity                | 10 to 90% @40°C , Non-condensing |
|             | Certification                   | CE/FCC Class A                   |

Note: All Specifications are subject to change without prior notice!

