

# Industrial Display Monitor

Open Frame Type

12.1" SVGA Open Frame Display Monitor

**TWAP-11260PD**



## Display Specifications

|                    |  |
|--------------------|--|
| Display            | 12.1" Color Active TFT Flat Panel Display                                |
| Luminance          | 300 cd/m <sup>2</sup>  |
| Viewing Angle      | 120 / 95 (H/V)   |
| Resolutions        | 800 x 600 ( native mode), 262K colors                                    |
| Backlight Lifetime | 50,000 hrs   |
| Touch Screen       | Analog resistive (optional)  |
| OSD Control        | On the back side   |
| I/O Connectors     | 1xDC power input, 1xVGA, optional:DVI,S-Video,RCA, touch (RS-232 or USB) |
| Power Input        | DC 12V, optional DC 11~28V   |

## Mechanical Specifications

|              |                          |
|--------------|--------------------------|
| Construction | Steel chassis            |
| Dimensions   | 300(W) x 250(H)x 38(D)mm |

## Environment Specifications

|                       |   |
|-----------------------|---|
| Operating Temperature | 0~50°C (32~122°F)                                 |
| Storage Temperature   | -20~60°C (-4~140°F)                               |
| Relative Humidity     | 10~90% @40 C Non-condensing, without touch screen |
| Vibration             | 1G peak, 5~500 Hz (Random)                        |
| Shock                 | 15G peak acceleration (11 msec. duration)         |
| Certificate           | Meet CE / FCC Class A                             |

## Dimensions

