

COMING SOON!

TOUCH
DYNAMIC

Summit

KIOSK

HIGHLIGHTS

- Exceptional **21.5" Widescreen** Portrait Display
- Mountable on **Wall, Counter, or Stand**
- Supports **Windows, Linux & Android 13 w. GMS**
- Self-Checkout Peripherals: **Scanner, Camera, LED Status Bar, Integrated Printer** & More



CONTACT US

888.508.6824 

contact@touchdynamic.com 

www.touchdynamic.com 

Summit

KIOSK

TOUCH
DYNAMIC

TECH SPECS

MOTHERBOARD	Alder Lake	Meteor Lake	G700
CPU/PROCESSOR	Intel® Alder Lake-N: N97, i3-N305	Intel® Meteor Lake Core Ultra 5 125U	MediaTek G700
MEMORY	8GB DDR4 (up to 32GB)	8GB DDR5 (up to 48GB)	8GB LPDDR4
STORAGE	256GB NVMe M.2 (up to 2TB)		64GB eMMC 1 x MicroSD slot
SUPPORTED OS	Windows 10 IoT LTSC, Windows 11 IoT LTSC, Windows 11 Pro, Linux, Android 13 w.o GMS		Android 13 w. GMS
I/O PORTS	2 x USB-A 3.0 4 x USB-A 2.0 1 x USB-C 2 x custom miniDP 3 x RJ48 Serial Port 1 x RJ45 LAN 1 x RJ11 Cash Drawer 1 x 4-PIN w. lock	4 x USB-A 3.0 2 x USB-A 2.0 1 x USB-C 2 x custom miniDP 3 x RJ48 Serial Port 1 x RJ45 LAN 1 x RJ11 Cash Drawer 1 x 4-PIN w. lock	4 x USB-A 2.0 1 x USB-C 1 x custom miniDP 1 x RJ48 Serial Port 1 x RJ45 LAN 1 x RJ11 Cash Drawer 1 x 2-PIN
WIRELESS CONNECTIVITY	(option) Wi-Fi & Bluetooth		Wi-Fi 6 & Bluetooth
AUDIO	1 x 3W Internal Speaker		
POWER	65W / 19V	120W / 19V	36W / 12V
DISPLAY	21.5" True-Flat PCAP Multi-Touch (1920 x 1080)		
PERIPHERAL (OPTIONS)	RFID Reader 3-Track MSR Storm ADA Compliant Key Pad Camera LED Status Bar 11.6" 2nd Display Mountable on wall, counter, stand, or back-to-back Honeywell Scanner Integrated Printer Options Payment Device Bracket		
ENVIRONMENT	Operating Temp: 32°F to 95°F (0°C to 35°C) Storage Temp: -4°F to 140°F (-20°C to 60°C) Humidity: 20%-85% non-condensing		
DIMENSIONS	TBD		

Product specifications and data are subject to change without notice.



888.508.6824

contact@touchdynamic.com

www.touchdynamic.com