

XF3-40

4-inch Direct Thermal
Shipping Label Printer



Print Characteristics

Print Method

Direct Thermal

Print Speed

Up to 6 ips (152 mm/sec)

Print Resolution

203 dpi

Print Width

Up to 108 mm

Print Length

Up to 1,000 mm

Sensor

Gap & Black mark (Fixed), Head Open,
Auto Paper Loading

Media Characteristics

Media Type

Gap, Black Mark, Notch, Continuous,
Fan-Fold

Media Width

25 to 116 mm

Media Roll Diameter

External roll media options up to 150 mm

Media Thickness

0.06 to 0.20 mm

Physical Characteristics

Dimensions (W x L x H)

198 x 80.5 x 82.5 mm
(7.80 x 3.17 x 3.25 inch)

Weight

0.94 kg (2.07 lbs.)

Electrical

EnergyStar® Certified,
External Power Adapter 100-240 VAC,
50/60 Hz

Performance Characteristics

Memory

8 MB SDRAM, 4 MB Flash

Interface

USB

Environment Characteristics

Temperature

Operating: 0 to 40°C (32 to 104°F)
Storage: -20 to 60°C (-4 to 140°F)

Humidity

Operating: 10 to 80% RH
Storage: 10 to 90% RH

Software

Emulation

SLCS™

Driver/Utility

Windows® Driver (Europlus),
Linux®/macOS® CUPS Driver,
BIXOLON Utility

Developer Tools

Windows SDK, Linux SDK,
Web Print SDK (Android/iOS/Windows/macOS)

Design & Print

Label Artist-II™, Label Artist™ Web

Fonts/Graphics/Symbologies

Fonts

Bitmap Fonts (10 SLCS),
Scalable Fonts (1 SLCS), 23 Code page

Downloadable Objects

Supporting user-defined fonts, graphics,
formats and logos

Barcode Symbologies

1D: Codabar, Code 39, Code 93,
Code 128, EAN-13, UCC/EAN128,
EAN-8, Interleaved 2-of-5, UPC-A,
UPC-E
2D: Data Matrix, MaxiCode, PDF417,
QR Code

Accessories/Supplies

Included in the Box

AC/DC Adapter, Power Cord, USB Cable

Options & Accessories

External Media Supply