

0700L 7-inch LCD

Touchscreen Monitor





Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 0700L 7-inch widescreen touchscreen monitor is designed to serve as a multifunctional unit with cost and space savings in mind. Whether used as a stand-alone or secondary display attached to a larger device, the 0700L can be applied to any environment, especially where a small screen is required. The 0700L is available with AccuTouch* five-wire resistive touch technology. Utilizing DisplayLink™ technology, the 0700L allows for power, video and touch signal through a single USB cable.

The optional web camera and three-track magnetic stripe reader (MSR), programmable to either HID or keyboard emulation (USB only) offer easy installation by the user, providing an elegant, integrated solution.

Available with AccuTouch five-wire resistive

IPX1 rated as resistant to dripping water; IP54 rated as resistant to particles and liquids

VESA mounting options

0700L 7-inch LCD Touchscreen Monitor

Specifications	Specifications		
Case/Enclosure/Bezel Color	Black		
Active Display Area	6.1" x 3.4" (154mm x 87mm)		
Dimensions	7.3" x 4.9" x 1.2" (187mm x 126mm x 31mm)		
LCD Technology	Active matrix TFT LCD		
Display Size	7" diagonal		
Native Resolution	800 x 480		
Aspect Ratio	16:9		
Number of Colors	16.7 million		
Number of Touches	Single-touch and non-touch		
Brightness (typical)	LCD Panel: 200 nits; with AccuTouch: 160 nits		
Response Time (Tr + Tf) (typical)	25 msec		
Viewing Angle (typical)	Horizontal: ±70° or 140° total; Vertical: +50° to -60° or 110° total		
Contrast Ratio (typical)	500:1		
Video	USB on Mini-B receptacle		
Input Video	Horizontal Sync frequency: 30KHz; Vertical Sync (frame rate) frequency: 60Hz		
Power	Monitor input power connector: USB Mini-B receptacle; Monitor input power signal specifications: 5V ±5%		
	Power Consumption (Typical): ON (monitor only): 4.5W; SLEEP (monitor only): 2.59W; OFF (monitor only, backlight off): 2.59W		
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit		
Weight	Unpackaged: 1.3lbs (0.59kg); Packaged: 1.9lbs (0.87kg)		
Shipping Dimensions	8.9" x 6.5" x 3.1" (225mm x 165mm x 80mm)		
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 60°C)		
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 10% to 90%		
Regulatory Approvals and Declarations	RCM; cUL, IC; CE; VCCI; NOM CoC; UL, FCC; CB; RoHS, WEEE; BSMI; KCC		
Warranty	3 years standard		
MTBF	50,000 hours demonstrated		
Other Features	IP1X drip-proof rating; IP54 rated for dust and water protection		
What's in the Box	USB Mini-B receptacle, User Manual CD, Quick Install Guide		

Ordering Information

Model	Part Number	Technology	Interface	Surface Treatment	Availability
0700L	E791658	AccuTouch	USB	Antiglare	Worldwide

Optional Peripherals / Accessories

Part Number	Description
E039290	Magnetic Stripe Reader (MSR)
E548382	Desktop Stand
E160104	Table top stand for 0700, 1002L and I-Series 10-inch
E412148	Bracket Kit for MSR
E750095	Mounting Bracket for Display compatible with the C-Series Touchcomputer
E332358	Mounting Bracket for 0700L as Rear-Facing Display
E075614	CABLE-KIT-2.5 Meter Y-Cable for the 0700L

Extended Warranty Options

Part Number	Description
758588-000	1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
930057-000	2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
E67295-000	Elo Advance Unit Replacement for Touchmonitors

To find out more about our extensive range of Elo touch solutions, go to **elotouch.com**, or call the office nearest you.

North America Tel +1 408 597 8000 Fax +1 408 597 8050 elosales.na@elotouch.com Europe
Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-PacificTel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin AmericaTel +1 786-923-0251
Fax +1 305-931-0124
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and AccuTouch are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17041AES00055

