



Z30 POS Stand

For I-Series Slate AiO



Integrated I/O



Concealed Cable Routing



Built-in CFD

Product Overview

The Z30 delivers a beautifully robust point-of-sale stand complete with an optional built-in customer-facing touchscreen display, integrated connectivity hub and concealed cable routing. With support for Elo's 15.6-inch Full HD I-Series Slate, available with Windows 10/11, ChromeOS Flex or Linux, the Z30 POS stand can easily be configured for point-of-sale.

Offer customers a point of interaction with an optional built in interactive CFD

Integrated connectivity hub built into the stand with a compartment for seamless cable routing

Compatible with the I-Series Slate 15.6-inch Full HD interactive display

Z30 POS Stand

Specifications	
Color	Dark Grey Metallic
Compatibility	Main Display: 15" I-Series 3 Slate with Intel (for use with E767561 and E768749) 15" I-Series 5 Slate with Android (for use with E767561, E768749, and E769881) Customer-Facing Displays (for use of non-CFD stand): 0702L – Elo P/N: E796382 1002L – Elo P/N: E155834 and E324341 1302L – Elo P/N: E683595 and E683787 1502L – Elo P/N: E125496
I/O Ports	DC Input 4 x USB-A 3.0 (900mA) RJ45 Ethernet LAN (Gigabit) RJ12 (Cash drawer)* 12/24V Powered USB 24V USB-C output - CFD (DisplayPort, Touch and Power Delivery up to 27W) *User will need to select mode
NFC	Front facing NFC antenna Programmable rear-lit LED illuminates NFC contactless logo (red, green, and white LED) Fully SoftPOS compatible
Display Head Connection	USB Type C
Power	AC input voltage: 100-240 VAC Input frequency: 50-60 Hz
Power Consumption	Without CFD: On: 1.2W; Off: <0.1W; Sleep: 1.2W With CFD: On: 6.5W; Off: <0.1W; Sleep: 2W With CFD & NFC: On: 6.5W; Off: <0.1W; Sleep: 2W
Dimensions (W x D x H)	E767561 & E768749: 9.68" x 7.85" x 6.46" / 245.8 mm x 199.3 mm x 164.2 mm E769881: 9.68" x 8.97" x 6.96" / 245.8 mm x 227.8 mm x 176.9 mm
Shipping Dimensions	12.0" x 11.5" x 12.4" / 305 mm x 292 mm x 315 mm
Weight	E767561: 4.85 lbs / 2.2 kg E768749: 5.51 lbs / 2.5 kg E769881: 6.20 lbs / 2.8 kg
Shipping Weight	E767561: 9.74 lbs / 4.4 kg E768749: 10.36 lbs / 4.7 kg E769881: 10.80 lbs / 4.9 kg
Temperature	Operating: 32°F to 104°F (0°C to 40°C) Storage: -4°F to 122°F (-20°C to 50°C)
Humidity	Operating: 20%-80% Storage: 5%-95%
MTBF	50,000 hours
Warranty	2 years standard
Extended Warranty	3 year warranty coverage - Elo P/N: E375367 4 year warranty coverage - Elo P/N: E375573 5 year warranty coverage - Elo P/N: E375771 2 year warranty coverage + AUR - Elo P/N: E375970 3 year warranty coverage + AUR - Elo P/N: E376169 4 year warranty coverage + AUR - Elo P/N: E376362 5 year warranty coverage + AUR - Elo P/N: E376547
Regulatory Approvals	FCC (US); IC (Canada); CE (Europe); VCCI (Japan); RCM (Australia)
What's in the Box	Z30 POS Stand, North America Power Cable, European Power Cable, Quick Install Guide, 150W Power Brick, 2 x Zip Ties, 2 x M4x6 mm screws in a plastic bag, 1 x M4x8 mm screw in a plastic bag, Base Plate - for mounting to a countertop

Built-In Customer-Facing Display

Specifications	
Size Resolution	10.1 inch 1200x1920 @ 60 Hz
Active Display Area	5.3" x 8.53" / 135.36 mm x 216.58 mm
Operating System	Horizontal: ±80° or 160° total / Vertical: ±80° or 160° total
Processor	LCD Panel: 450 nits; TouchPro PCAP: 387 nits
Number of Colors	8-bit (16.7M)
Touch Technology	TouchPro® PCAP (Projected Capacitive) - up to 10 touches
Sealing	Touchscreen sealed to LCD

Ordering Information

Part Number	Customer-Facing Display
E767561	Z30 POS Stand Without CFD
E768749	Z30 POS Stand With CFD
E769881	Z30 POS Stand With CFD & NFC

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.
© 2024 Elo Touch Solutions, Inc. All rights reserved. 26011AES00181

