

O15AX

Open Frame Projected Capacitive Touch Displays



Features:

- Rugged and durable steel enclosure
- Excellent optical performance
- Zero pressure touch activation
- Multiple sizes available - 15", 17", 19", 22", and 24"
- Wide screen sizes also available in 15" and 19"
- 3 year warranty

Specifications

Part Number	O15AX
Display Size	15 in
Display Area	12 x 9 in (304.1 x 228.1 mm)
Panel Brightness (With PCAP Sensor)	300 nits (258 nits)
Response Time	12 ms Typical (Tr + Tf)
Power Consumption	12W MAX Standby ≤ 0.5W
Dimensions (W x H x D)	13.9 x 11.2 x 1.8 in (352.6 x 284 x 45.2 mm)
Weight	9.9 lbs (4.5 kg)
Contrast Ratio	700:1
Native Resolution	1024 x 768
Aspect Ratio	4:3
Viewing Angle	160°H / 130°V
Touch Material	2 mm Glass
VESA Mount	100 x 100 mm
Video Inputs	HDMI, DVI, VGA
Backlight	LED
Input Power	12VDC ± 5% (Adapter Input AC 100V ~ 240V, 50/60Hz)
MTBF	50,000 hrs
Touch Type	Projected Capacitive (PCAP), SAW Optional
Touch Points	10 max (Dependent on OS / Browser / Software)
Touch Accuracy	2 mm
Touch Interface	USB (B-Type)
Surface Durability	Mohs' 7H
Temperature	Operating: 32°F ~ 104°F (0°C ~ 40°C) Storage: -4°F ~ 140°F (-20°C ~ 60°C)
Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
Enclosure Material	Metal Enclosure
Included Accessories	AC Adapter, Power Cable, VGA / USB Cables

Mechanical Drawing

