



ELITE POS | 635080

LogicTouch Elite

All-in-One POS Terminal

FEATURES

- + Supports Windows, Chrome and Linux
- + Intel® i3-N305 Processor
- + 15.6" 1920 x 1080 resolution screen
- + 11.6-inch Customer Facing Screen (optional touch)
- + True-Flat PCAP multi-touch screen
- + Heat Resistance up to 140° F (60° C)
- + 3-Year Warranty

All-in-One Terminal

The touchscreen LogicTouch Elite 15.6" All-in-One POS Terminal features a sharp high-definition screen plus a second 11.6" customer-facing screen for an enhanced experience during checkout. The second screen can increase sales and engagement with marketing messages, special deals, and more during the checkout experience.

Engineered with high-performance Intel® i3 processor and featuring native support for Windows, Android and Linux, this Elite POS model has the power to support demanding applications and also ships with a variety of ports for easy connectivity to accessories.

logiccontrols.com



LogicTouch Elite POS Specifications

SYSTEM

Processor: Intel® i3-N305
Memory: 1 x DDR4 SO-DIMM - 16 GB
Storage: 128 GB SSD
Expansion: 1x M.2 M Key for SATA or NVME SSD

DISPLAY

Size and Resolution: 15.6" 1920 x 1080
2nd Display 11.6" 1920 x 1080
Touch Screen: True-Flat PCAP multi-touch

I/O PORTS

USB-Type A: 4 x USB 2.0; 2 x USB 3.0
USB-Type C: 1 x USB 3.0 full-functioned (DP / PD 5V/3A,12V/1.5A)
Serial Port: 3 x RJ50 (standard RS232) (default 0V; 5V, 12V)
LAN: 1 x RJ45
Cash Drawer: 1 x RJ11
DC Jack: 1 x 4PIN (with latch)

OPTIONAL I/O

Powered USB: 2 x Powered USB 12V & 1x Powered USB 24V

POWER

Power Adapter: 65W/19V (120W/19V with 2x PUSB 12V & 1x PUSB 24V)

PERIPHERAL (OPTION)

MSR: 3-Track MSR (USB)
Fingerprint: Fingerprint reader (USB)
iButton: iButton (USB)

CERTIFICATE

EMC & Safety: FCC Class A, CE Mark, LVD

ENVIRONMENTAL

Operating temperature: 0°C ~ 35°C (32°F ~ 95°F)
Storing temperature: -20°C ~ 60°C (-4°F ~ 140°F)
Relative humidity: 20% ~ 85% RH non-condensing

DIMENSIONS

(L x W x D): **Without Stand:** 369.28mm x 234.26mm x 35.75mm (14.54in. x 9.22in. x 1.41in.)
(L x W x H): **With Stand:** 369.28mm x 188.65mm x 294.31mm (14.54in. x 7.43in. x 11.59in.)
Active Screen Area:

Weight: **Without Stand:** 6.2lbs (2.81 KG)
With Stand: 10.4lbs (4.72 KG)

MOUNTING

VESA Mount: 100 x 100

OS SUPPORTED Windows 10 IoT Enterprise (Optional Windows 11), Linux, ChromeOS

