



PRO POS N97 | 650457

# LogicTouch Pro

All-in-One Terminal

## FEATURES

- + Supports Windows, Android, and Linux
- + Powerful Intel® N97 Processor
- + 15.1" 1028 x 768 resolution screen
- + True-Flat PCAP multi-touch screen
- + IP54 Rated for Water and Dust Resistance
- + Heat Resistance up to 140° F (60° C)
- + Includes foldable stand base
- + 3-Year Warranty

## All-in-One Terminal

The touchscreen LogicTouch Pro 15" All-in-One is designed with the cost-effective flexibility you need to power most retail and restaurant checkouts.

Engineered with high-performance Intel® N97 processor and featuring native support for Windows, Android and Linux, this Pro POS model also ships with a variety of ports for easy connectivity and includes a foldable stand base.



# LogicTouch Pro Specifications

## SYSTEM

Motherboard: F35  
Processor: Intel®N97  
Memory: 1 x DDR4 up to 32 GB (8 GB standard)  
Storage: 128GB SSD (M.2)  
Expansion: 1 M.2 (E Key)

## DISPLAY

Size and Resolution: 15.1" 1024x768  
Touch Screen: True-Flat PCAP multi-touch

## I/O PORTS

USB-Type A: 4 x USB2.0; 2 x USB3.0  
USB-Type C: 1 x USB3.0 full-functioned (DP / PD 5V/3A,12V/3A)  
Serial Port: 3 x RJ48 (standard RS232) (default 0V; 5V,12V)  
LAN: 1 x RJ50  
Cash Drawer: 1 x RJ11  
DC Jack: 1 x 4PIN (with latch)

## OPTIONAL I/O

Powered USB: 2 x Powered USB 12V & 1x Powered USB 24V

## POWER

Power Adapter: 65W/19V (120W/19V with 2x PUSB 12V & 1x PUSB 24V)

## INDICATOR

LED Indicator: 1  
Power Button: 1

## PERIPHERAL (OPTION)

MSR: 3-Track MSR (USB)  
Fingerprint: Fingerprint reader (USB)  
iButton: iButton (USB)  
Customer Display: LCM display 2 x 20 characters (USB)  
2nd Display: 11.6" 2nd display

## CERTIFICATE

EMC & Safety: FCC Class A, CE Mark, LVD

## ENVIROMENTAL

Operating temperature: 0°C ~ 35°C (32°F ~ 95°F)  
Storing temperature: -20°C ~ 60°C (-4°F ~ 140°F)  
Relative humidity: 20% ~ 85% RH non-condensing

## DIMENSIONS

W x H x D: 369 x 277 x 203 mm (14.2" x 10.9" x 8.0")  
Weight: 4.3 kg (9.5 lbs)

## MOUNTING

VESA Mount: 100 x 100

**OS SUPPORTED** Windows 10 IoT Enterprise, Linux, Android, ChromeOS

