




Mimo Open Frame Display with BrightSign Built-In with HD Series 5 Player

10"-32" MBS Series. See Part Numbers in the Available Screens, Sizes and Options section



A truly brilliant, smart, and professional tablet With BrightSign HS125 Player Built-In Digital Signage Module



The Mimo Wide Viewing Angle Digital Signage Display

Two trusted powerhouse digital signage leaders - Mimo and BrightSign - have teamed up to deliver the Mimo Display with BrightSign Built-In. This versatile and reliable, all-in-one digital signage solution leverages the power of Mimo display technology with the industry-leading BrightSign platform. The result is a high-quality, easy-to-install solution that's immediately digital signage ready, making it extremely simple to use, especially for those already reliant on the BrightSign platform. The Mimo Display with BrightSign Built-In features a modern zero bezel design, a nearly 180-degree viewing angle from its bright, high-contrast IPS screen, and a range of resolutions that can display in either landscape or portrait orientations. HD resolution and common VESA patterns available where wall or desktop mounting is desired. Ask a Mimo rep about mounting ears for kiosk applications.

BrightSign Built-In

The BrightSign Built-In Digital Signage Module is an HD Series 5 class Bright Sign player compatible with all BrightSign software, services and supported CMS solutions, and a global network of partner CMS solutions and integrations. Simplify installation with an all-in-one solution that minimizes cabling and setup time and seamlessly embeds into small and large format displays with Full HD or 4K options. Operates with unparalleled reliability, security and sustainability on BrightSign OS while reducing total cost of ownership with complimentary remote player management and controls.

Features:

- PCap Touch Screen and Non-Touch Options
- POE Options 10.1" through 23.8"
- Same Mounting Options as M Series
- TAA Compliant
- 10-point capacitive touchscreen (optional)
- Mechanical drawings available upon request
- S/PDIF digital audio
- Engaging interactive controls via CPIO and UDP
- 1x USB 2.0
- Serial and IR control for expanded interactive options
- WiFi / Bluetooth Module (optional) MCT-WIFI2-OPT enables solution to network using WiFi and operate Bright Beacon via Bluetooth
- Video engine (HS125 supports Full HD 1080p60 single decode)
- Low-power, fan-less design
- HDMI output (HS125 supports 1.4) with CEC
- Mainstream HTML5 Engine
- 100baseT Ethernet
- CEC Power Management



- Cloud-based subscription included with all MBS Series BrightSign displays
- Streamlined player setup
- Real-time player health and controls
- Your choice of CMS
- Free subscription with MBS Series Display!
- Annual BrightSign subscription n/a Mimo
- Includes Cloud Control services
- Adds a complete set of content and network management tools
- **Free 30-day trial**



Product Specifications

	HS125
I/O Package	Expanded I/O
AI ENABLEMENT	
Neural Processing Unit (NPU)	X
VIDEO & HTML5 ENGINES	
4K video decoding	
Full HD at 60p video decoding	X
HTML support: HTML5, CSS, JavaScript, SVG, WebGL, and Chromium compatible	X
Supports 4K IP streaming	X
MEDIA FORMATS	
4K Video codecs: H.265, H.264	X
4K Video Containers: .ts, .mov, .mp4, .mkv	X
Full HD Video Codecs: H.265, H.264 (MPEG-4, Part 10), MPEG-2	X
Full HD Video Containers: .ts, .mpg, .vob, .mov, .mp4, .m2ts	X
Images: BMP, JPEG, PNG	X
Audio: MP2, MP3, AAC and WAV (AC3 is passed through)	X
DISPLAY RESOLUTIONS	
Supports all common screen resolutions	X (up to Full HD)
Supports additional & customizable display resolutions with unique aspect ratios	X
ACCESSORIES	
BP200 & BP900 USB Button Pads	
WD-105 Dual Antenna Wireless/Bluetooth Module	X
MicroSD Class 10 Cards (various capacities)	X
BrightSign Mobile USB Modem & Service	X
MISCELLANEOUS	
Dimensions (W x D x H)	100 x 70 x 14.25 mm
Power Supply	12V / 1.5A
Multi-Country Power & Regulatory Approvals	X
Built-in Wall Mounting	X
Included 5-Year Warranty, parts and labor*	X

Available Screens, Sizes & Options

	C PCAP touch	POE w/POE	L w/LED	OF Open Frame	WF w/WiFi
MBS-1080	✓	✓	✓	✓	✓
MBS-15680	✓	✓		✓*	✓
MBS-21580	✓	✓		✓*	✓
MBS-23380	✓	✓		✓*	✓
MBS-27080	✓			✓*	✓
MBS-32080	✓			✓*	✓

- ✓* Only option. All are open frame, desktop and wall mountable
- ✓ Available Options

Part Number Example:

MBS-21580-OF-POE = a 21.5" non-Touch, with POE

MBS-21580C-POE-WF = 21.5" PCap touch, with POE, with WiFi

BrightSign Features

 1080p60 single decode	 H.265	 Mainstream HTML5	 IP Streaming	 BrightBeacon™	 BrightWall™	 AutoWall™
 Zones	 Interactive	 Live Feeds	 Geo-Fencing	 Tagging	 BrightSign App	 Sign Preview
 Remote Snapshot	 B-Deploy	 Digital Audio	 Mosaic Mode			