

Android Terminal

L2 5" Hand-Held Computer

The L2 is a robust, hand-held computer built for mobile data collection. A built in 2D scanner with a dedicated scan button make it an ideal solution for warehousing and AIDC. The 4 foot drop rating and IP67 seal protect against any sort of accidents, including being submerged in water up to 3 feet.



ANDROID NOUGAT

Android 7.1 with Google Play services ensure compatibility with your application right out of the box



BUILT-IN SCANNER

An integrated 2D barcode scanner provides data collection on the go.



CLOUD DEVICE MANAGEMENT

Fully customize your user's out of box experience with pre-installed apps



ROBUST CONSTRUCTION

Withstands multiple drops to concrete, and an IP67 rating protects from being submerged in water



PART NUMBER	AND-L2C
CPU	Qualcomm Snapdragon 425 Quad-core
OS	Android 7.1
Memory	2GB RAM
Storage	16GB Storage
Display	5" Multi-Touch Capacitive Touch
Display Resolution	IPS 1280x720
Wireless LAN	Dual band 2.4g/5g 802.11 a/b/g/n
Cellular Radios	GSM/WCDMA 2G(850/900/1800/1900), WCDMA 3G (900/2100 or 850/1900) 4G LTE (Band 2/4/7/17/28)
SIM Card	1 x Standard Size
Bluetooth	2.1/3.0/4.0 and BLE
Speaker	1 @ 1W
Battery	8 Hours, 5000 mAh, with Qualcomm Quick Charge
GPS	GPS and AGPS
Camera	5MP, Rear facing
Barcode Scanner	Supports Aztec, Codabar, Code 11, Code 128, Code 39, Code93, DataBar, Discrete 2 of 5, EAN8, EAN13, ISBN, UPC-A, UPC-E, ITF, Datamatrix, MaxiCode, MSI Plessey, PDF417, QR, US Post Net,
NFC	Mifare/Felica/ISO 14443/ Type A/B/ISO15693

PORTS	
USB	1 x USB C
Audio	1 x 3.5mm Headphone

WARRANTY EXTENSION AND UPGRADES	
ZWE-TPC	2-Year warranty extension
ZOE-TPC3	**Next business day protection
ZOE-TPC5	**2-Year warranty extension + Next business day protection

*Actual formatted space will be less, OS and built in apps require space
 **Available in USA and Canada.

PHYSICAL	
Dimension (WxDxH)	2.9" x 0.6" x 5.9" (75mm x 17mm x 150mm)
Weight	0.52 lb (240g)
Color	Black and Orange
Electrical	AC 100 ~ 240V 0.15 A (input) DC 5V / 1A (output)
Buttons	Power, Volume Up, Volume Down, Home, and Scan

ENVIRONMENTAL	
Temperature	Operating: -4°F to 131°F (-20°C to 55°C) Storage: -40°F to 140°F (-40°C to 60°C)
IP Rating	IP67, Submerged up to 3 feet in water, sealed from dust
Drop Rating	Multiple drops to concrete from up too 4 feet
Warranty	1-year warranty
Certifications	FCC, CE, CCC