




SOCKETSCAN® S860



2D/1D Imager



Passport Reader

OCR-A
1234ABCD

Alphanumeric
(+4 currency char.)

OCR-B
1234ABCD

Alphanumeric
(+4 currency char.)

MICR E-13B
123456789

Numeric
(+4 special char.)

OCR-A / OCR-B / MICR E13B

Thin, Small & Light - Great for one-handed solutions

The Socket Mobile S860 is a fast-scanning 2D imager barcode scanner and passport reader with Bluetooth® wireless technology. The scanner virtually captures any 1D or 2D barcodes in milliseconds. Small, thin and easy to use, the scanner is optimized for attaching to mobile devices, enabling one-handed operation. Merchants can scan barcodes of products and the passports of consumers with one device. Scanning barcodes printed on labels or displayed on device screens, it reads all the most popular 2D barcodes and MRZ/passports, perfect for the travel industry retail point of sale, inventory management, sales order entry, field service, and other mobile business applications. Approximately the same size as a credit card, measuring less than ½ inch (1.27cm) thick and weighing less than two ounces, the S860 is one of the smallest and lightest barcode scanners and passport readers available in the market today. The S860 slips neatly into your pocket and fits comfortably in the palm of your hand when attached to a smartphone.




 **Bluetooth®**


Certified by Apple® for iOS devices (iPad®, iPhone®, iPod Touch® devices) and compatible with Android and Windows®

Features

- **Bluetooth Wireless Technology** - Connects easily to a wide range of Bluetooth enabled smartphones, tablets, notebook and desktop computers
- **Certified by Apple® for iOS devices** - Guaranteed Compatibility - With our SDK integrated in over 700+ applications, Socket Mobile scanners are one of the most natively integrated scanners available today. Socket Mobile Scanners are also 100% compatible with any application out-of-the-box in HID (keyboard emulation) mode.
- **Compatible with all Android and Windows devices and applications**
- **Scanning** - Fast 2D & 1D barcode scanning with highly visible and safe LED aimer and omni-directional ability, allowing intuitive rapid scanning. Scans OCR A&B fonts, OCR USC, OCR passport and OCR MICR (E13B) fonts.
- **LED Aimer** - Bright, rectangular illumination field with LED dot for precise aiming.
- **Size & Weight** - Measuring less than ½ inch (1.27cm) thick and weighing less than two ounces (48g)
- **User Feedback** - With audible tones, hand pulsation and Bluetooth indicators
- **Long-Lasting Battery** - Power to last over 16 hours
- **One-Handed Operation** - Attachable clip included
- **Protective Material** - Made with antimicrobial material for protection against potentially harmful bacteria
- **Application Integration** - Socket Mobile's Capture SDK enables easy integration in your applications to improve business productivity with fast, efficient and reliable data transfer over Bluetooth wireless technology
- **Accessories** - DuraCase, lanyard and wrist strap available (sold separately)
- **Designed and Assembled in the USA**
- **Developer Support Available**
- **1-Year Warranty**

PHYSICAL CHARACTERISTICS



Default Barcode Symbologies:	1D Symbologies: Codabar, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, UPC A, UPC EO 2D Symbologies: Aztec, Data Matrix, Maxicode, Micro PDF417, PDF417 Postal Codes: Australia Post OCR Type Face: OCR Passport - 2 lines																					
Supported Barcode Symbologies:	1D Symbologies: Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Composite CC-A/B, Composite CC-C, Composite TLC, Discrete 2 of 5, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, ISSN EAN, Matrix 2 of 5, MSI, UPC/EAN/JAN, UPC A, UPC EO 2D Symbologies: Aztec, Data Matrix, Maxicode, Micro PDF417, MicroQR, PDF417, QR Code Postal Codes: Australia Post, Han Xin, Japan Postal, KIX Code, Maxicode, Netherlands, UPU FICS Posta, US Planet, US Postnet, USPS 4CB/One Code/Intelligent Mail OCR Type Face: OCR-A, OCR-B, MICR-BBB, US currency serial number																					
Scan Angle:	Horizontal: 42° Vertical: 28°																					
Sensor Resolution:	1280 x 800 pixels																					
Print Contrast:	Down to 25%																					
Reading Distance:	 <p>Diagram illustrating the Depth of Field for various barcode symbologies. The S860 scanner is shown at the left edge of a series of bars. The bars represent different symbologies and their widths: C128 (5 mil), PDF 417 (5 mil), Code 39 (4 mil), Data Matrix (10 mil), Code 39 (5 mil), 100% UPC A, and Code 39 (20 mil). The distance from the scanner to the first bar is 2.8 inches (7.1 cm), and to the last bar is 30.0 inches (76.2 cm). The diagram also includes a scale bar from 0 to 30 inches/cm and a note that the field of view is limited.</p> <p>4.6 to 76.2 cm (1.8 to 30.0 in.) Depends on barcode size, symbology, label media, Narrow and Wide ratio, scan angle</p>																					
Decode Ranges	<table border="1"> <thead> <tr> <th></th> <th>Near</th> <th>Far</th> </tr> </thead> <tbody> <tr> <td>4 mil Code 39</td> <td>3.3 in/8.4 cm</td> <td>8.8 in/22.4 cm</td> </tr> <tr> <td>5 mil Code 128</td> <td>2.8 in/7.1 cm</td> <td>8.2 in/20.8 cm</td> </tr> <tr> <td>5 mil Code 39</td> <td>2.0 in/5.08 cm</td> <td>13.5 in/34.3 cm</td> </tr> <tr> <td>10 mil Data Matrix</td> <td>2.9 in/7.4 cm</td> <td>10.1 in/25.7 cm</td> </tr> <tr> <td>100% UPC A</td> <td>1.8 in/4.6 cm*</td> <td>26.0 in/66.0 cm</td> </tr> <tr> <td>20 mil Code 39</td> <td>2.0 in/5.08 cm*</td> <td>30.0 in/76.2 cm</td> </tr> </tbody> </table>		Near	Far	4 mil Code 39	3.3 in/8.4 cm	8.8 in/22.4 cm	5 mil Code 128	2.8 in/7.1 cm	8.2 in/20.8 cm	5 mil Code 39	2.0 in/5.08 cm	13.5 in/34.3 cm	10 mil Data Matrix	2.9 in/7.4 cm	10.1 in/25.7 cm	100% UPC A	1.8 in/4.6 cm*	26.0 in/66.0 cm	20 mil Code 39	2.0 in/5.08 cm*	30.0 in/76.2 cm
	Near	Far																				
4 mil Code 39	3.3 in/8.4 cm	8.8 in/22.4 cm																				
5 mil Code 128	2.8 in/7.1 cm	8.2 in/20.8 cm																				
5 mil Code 39	2.0 in/5.08 cm	13.5 in/34.3 cm																				
10 mil Data Matrix	2.9 in/7.4 cm	10.1 in/25.7 cm																				
100% UPC A	1.8 in/4.6 cm*	26.0 in/66.0 cm																				
20 mil Code 39	2.0 in/5.08 cm*	30.0 in/76.2 cm																				

- (1) SocketScan S860, 1D Imager Barcode Scanner
- (1) Micro USB Charging Cable
- (1) Universal Klip Case
- (1) Get Started Insert



OPTIONAL ACCESSORIES

DuraCase Only
 Apple® iPod touch® for 5th/6th gen
 Samsung J3/J5
 Samsung Galaxy S7



DuraCase & Charging Dock
 Apple® iPod touch® for 5th/6th generation
 Samsung J3/J5
 Samsung Galaxy S7



Holster



DuraCase Charging Adapter



DuraCase Charging Dock



DuraCase 6 Multi-Bay Charger



DuraCase 6 Multi-Bay Charger
 AC Power Cord



Klip Cases

iPhone SE/5/5s

iPhone 5c

iPod touch(5th generation)

Samsung Galaxy S4



Lanyard - Black



Technology: 2D/1D Barcode Imager & OCR character reader

Light Source Aimer: Hyper red 660 NM (nanometer) LED 6/0 NM LED

SCANNER TYPE

Battery:	Lithium ion rechargeable battery
Charge Time:	4 Hours
Battery Life:	Standby time: 25 hours
Per Full Charge:	Active Scan Time: 34,000 scans within 3 hours (based on 2 scans every 1 second) or 9,000 scans within 10 hours (based on 1 scan every 4 seconds)
Note:	Battery life varies depending on ambient temperature, ambient light, age of battery, etc.

WARRANTY

Scanner:	Standard one year limited warranty
Accessories:	90 days
Extended Warranty: (sold separately)	www.socketmobile.com/socketcare



COMMON USES

Retail	Hospitality	Point of Sale
Logistics	Life Sciences	Automotive
Healthcare	Travel	

BLUETOOTH (WIRELESS CONNECTION) 

Bluetooth Radio:	Class 2 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption
Bluetooth Range:	Up to 10 m (33 ft.) depending on environment, range limit is usually due to the Host Device (phone, tablet or notebook)
Bluetooth Profiles:	Basic Mode - Human Interface Device (HID)*, Application Mode - Serial Port Profile (SPP) and Application Mode - MFi-SPP. Some Operating Systems or smartphone/tablet models may support only one profile. <i>*By default, the scanner is set to Basic Mode (HID).</i>

PHYSICAL CHARACTERISTICS

Dimensions:	3.42 (L) x 2.12 (W) x .52 (H) in (86.9 x 53.94 x 13.43 mm)
Weight/Mass:	1.7 oz (48 g)
LEDs:	Scan LED: Green and Red Bluetooth LED: Blue
Buttons:	Scan Button: Scan Power Button: On/Off

USER ENVIRONMENT

Ambient Light:	From 0 to 100,000 lux From pitch black to direct sun light
Operating Temperature:	+32 to +122 °F (0 to +50 °C)
Storage Temperature:	-22 to +158 °F (-30 to +70 °C)
Relative Humidity:	5% to 95% (non condensing)
Sealing:	IP40
Drop Specifications:	Multiple 3.3 ft. drops to vinyl covered concrete

OPERATING SYSTEM COMPATIBILITY

Android OS: Basic Mode (HID)* & Application Mode (SPP)

Mac OS: Basic Mode (HID)* only

Apple iOS: Basic Mode (HID)* & Application Mode (MFi-SPP)

Windows: 10, 8, and 7: Basic Mode (HID)* & Application Mode (SPP)

Compatible with devices supporting Basic Mode (HID)* protocol

*By default the scanner is in Basic Mode (HID).

Certified by Apple® for iOS devices (iPad®, iPhone®, iPod Touch®) and compatible with Android and Windows®.

iOS



OS X



CERTIFICATION & REGULATORY

Electrical Safety: Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2

Environmental: RoHS compliant

EMI / RFI: FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC

LED Safety: IEC 60825-1, EN 60825-1

FCC: T9J-RN42



IC: 6514A-RN42
Telec ID: 2017-5709



socketmobile.com

Toll-Free: +1 800 552 3300 (USA/Canada)

France: +33 970 462 241

Latin America: +1 510 933 3153

sales@socketmobile.com

Asia Pacific: +1 510 933 3122

Germany: +49 9401 5299 052

Switzerland: +41 62 834 07 80

EMEA & Russia: +41 62 834 0780

Japan: +8190 9808 0518

UK/Ireland/South Africa: +44 (0) 1252 761403

+44 7787 112109